

**MONTANA HIGHWAY PATROL  
TOW TRUCK INSPECTION REPORT**

FIRM NAME \_\_\_\_\_ TAX ID # \_\_\_\_\_

FIRM ADDRESS \_\_\_\_\_

YEAR \_\_\_\_\_ MAKE \_\_\_\_\_ VIN \_\_\_\_\_ LICENSE PLATE \_\_\_\_\_

TRUCK CLASSIFICATION: CLASS A  CLASS B  CLASS C  CLASS D

CURRENT HQ MV-5 ON FILE? YES  NO

CVSA LEVEL 1 INSPECTION (MANDATORY) FORM 63 # \_\_\_\_\_ (OPTIONAL) CVSA DECAL # \_\_\_\_\_

MCS INSPECTION COMPLETED YES  NO

YES NO

**MINIUM REQUIREMENTS FOR ALL TOW TRUCKS**

- |  |                          |                          |
|--|--------------------------|--------------------------|
| 1. MINIMUM TWO FLARES, FLAGS, LANTERNS, REFLECTORS, OR OTHER APPROVED WARNING DEVICE . . . . . | <input type="checkbox"/> | <input type="checkbox"/> |
| 2. MINIMUM TWO 3' X 3' REFLECTORIZED SIGNS (RECTANGULAR WITH AN ORANGE BACKGROUND) . . . . .   | <input type="checkbox"/> | <input type="checkbox"/> |
| (APPROVED WORDAGE "WRECK AHEAD" OR "TOW TRUCK AHEAD" OR "WRECKER AHEAD") WITH 5" LETTERING     |                          |                          |
| 3. MINIMUM FIVE LB DRY CHEMICAL FIRE EXTINGUISHER(S) OR EQUIVALENT . . . . .                   | <input type="checkbox"/> | <input type="checkbox"/> |
| 4. ONE OPERATING RED OR AMBER LIGHT . . . . .  | <input type="checkbox"/> | <input type="checkbox"/> |
| 5. MINIMUM OF ONE BROOM . . . . .  | <input type="checkbox"/> | <input type="checkbox"/> |
| 6. MINIMUM OF ONE SHOVEL . . . . .   | <input type="checkbox"/> | <input type="checkbox"/> |
| 7. EXTENSION CORD OR OTHER DEVICE ILLUMINATING STOP/TURN/TAIL LIGHTS ON TOWED UNIT . . . . .   | <input type="checkbox"/> | <input type="checkbox"/> |
| 8. TWO WAY RADIO, MOBILE OR CELLULAR PHONE . . . . .   | <input type="checkbox"/> | <input type="checkbox"/> |
| 9. ONE SNATCH BLOCK PER LINE . . . . .   | <input type="checkbox"/> | <input type="checkbox"/> |

**CLASS A REQUIREMENTS (MUST MEET 1 THROUGH 9 ABOVE, PLUS)**

- |   |                          |                          |
|---|--------------------------|--------------------------|
| 10. MINIMUM GVWR OF 10,000 LBS OR MORE ON TRUCK CHASSIS . . . . .   | <input type="checkbox"/> | <input type="checkbox"/> |
| 11. DUALS ON REAR AXLE (SINGLE REAR WHEELS WILL BE ACCEPTED IF IN SERVICE PRIOR TO 10/01/1995.) . . . . . | <input type="checkbox"/> | <input type="checkbox"/> |
| 12. AT LEAST ONE WINCH DRUM (RECOMMEND) 3/8" WIRE ROPE) . . . . .   | <input type="checkbox"/> | <input type="checkbox"/> |
| 13. A DUAL OR SINGLE BOOM WITH A RATE CAPACITY OF FOUR TONS . . . . .                                     | <input type="checkbox"/> | <input type="checkbox"/> |
| 14. A PORTABLE DOLLY CAPABLE OF HAULING UNTOWABLE VEHICLES . . . . .                                      | <input type="checkbox"/> | <input type="checkbox"/> |
| 15. IF EQUIPPED WITH WHEEL LIFT (1,500 LB CAPACITY FULLY EXTENDED) . . . . .                              | <input type="checkbox"/> | <input type="checkbox"/> |

**CLASS B REQUIREMENTS (MUST MEET 1 THROUGH 9 ABOVE, PLUS)**

- |   |                          |                          |
|---|--------------------------|--------------------------|
| 16. MINIMUM GVWR OF 18,000 LBS OR MORE ON TRUCK CHASSIS . . . . .                 | <input type="checkbox"/> | <input type="checkbox"/> |
| 17. DUALS ON REAR AXLE . . . . .  | <input type="checkbox"/> | <input type="checkbox"/> |
| 18. A DUAL OR SINGLE BOOM WITH A RATED CAPACITY OF EIGHT TONS . . . . .           | <input type="checkbox"/> | <input type="checkbox"/> |
| 19. IF EQUIPPED WITH WHEEL LIFT (4,000 LB LIFT CAPACITY FULLY EXTENDED) . . . . . | <input type="checkbox"/> | <input type="checkbox"/> |
| (A CLASS A WHEEL LIFT SYSTEM IS ACCEPTABLE IF USED TO TOW CLASS A VEHICLES ONLY)  |                          |                          |
| 20. ONE WINCH DRUM (RECOMMEND 7/16" WIRE ROPE) . . . . .                          | <input type="checkbox"/> | <input type="checkbox"/> |

**CLASS C REQUIREMENTS (MUST MEET 1 THROUGH 9 ABOVE, PLUS)**

- |  |                          |                          |
|--|--------------------------|--------------------------|
| 21. MINIMUM GVWR OF 32,000 LBS OR MORE ON TRUCK CHASSIS . . . . .                                | <input type="checkbox"/> | <input type="checkbox"/> |
| 22. DUALS ON REAR AXLE . . . . .   | <input type="checkbox"/> | <input type="checkbox"/> |
| 23. MINIMUM OF 16 TON SINGLE OR DUAL BOOM . . . . .  | <input type="checkbox"/> | <input type="checkbox"/> |
| 24. MINIMUM OF ONE WINCH DRUM (RECOMMEND 9/16" WIRE ROPE) . . . . .                              | <input type="checkbox"/> | <input type="checkbox"/> |
| 25. EQUIPPED WITH AIR BRAKE SYSTEM CAPABLE OF SUPPLYING AIR TO TOWED VEHICLE . . . . .           | <input type="checkbox"/> | <input type="checkbox"/> |
| 26. IF EQUIPPED WITH WHEEL LIFT SYSTEM (MINIMUM 8,000 LB LIFT CAPACITY FULLY EXTENDED) . . . . . | <input type="checkbox"/> | <input type="checkbox"/> |

**CLASS D REQUIREMENTS (MUST MEET 1 THROUGH 9 ABOVE, PLUS)**

- |   |                          |                          |
|---|--------------------------|--------------------------|
| 27. ONE 4-TON WINCH (6 X 19, 26, 37 3/8 WIRE ROPE RECOMMENDED) . . . . .                | <input type="checkbox"/> | <input type="checkbox"/> |
| 28. ONE FIVE FOOT CHAIN (RECOMMEND GRADE 8) . . . . .                                   | <input type="checkbox"/> | <input type="checkbox"/> |
| 29. MINIMUM OF FOUR SECURING DEVICES EACH WITH WORKING LOAD LIMIT OF 3,500 LBS. . . . . | <input type="checkbox"/> | <input type="checkbox"/> |

SIGNATURE OF TROOPER \_\_\_\_\_

ID# \_\_\_\_\_

SIGNATURE OF OPERATOR/OWNER \_\_\_\_\_

DATE \_\_\_\_\_